

## BBCV2.MH49776 Lithium Batteries - Component

[Page Bottom](#)

### Lithium Batteries - Component

[See General Information for Lithium Batteries - Component](#)

**RONDA GROUP CO LTD**

MH49776

BLK C & D  
SHACHONGWEI INDUSTRIAL ZONE  
HUANGZHUANG JIANSHE THIRD RD  
JIANGMEN, GUANGDONG 529000 CHINA


Model No.	Secondary Type <sup>[d]</sup>	Max Charging Current (I <sub>c</sub> ), mA	Max Charging Voltage, V dc <sup>[e]</sup>	Test Compliance <sup>[f]</sup>
RD IFR10440-200	Lithium ion (Cylindrical)	200	3.7	1
RD IFR10440-240	Lithium ion (Cylindrical)	240	3.7	1
RD IFR12500-350	Lithium ion (Cylindrical)	350	3.7	1
RD IFR14280-320	Lithium ion (Cylindrical)	320	3.7	1
RD IFR14430-500	Lithium ion (Cylindrical)	500	3.7	1
RD IFR14500-600	Lithium ion (Cylindrical)	600	3.7	1
RD IFR14500-650	Lithium ion (Cylindrical)	650	3.7	1
RD IFR14650-800	Lithium ion (Cylindrical)	800	3.7	1
RD IFR14650-950	Lithium ion (Cylindrical)	950	3.7	1
RD IFR18500-1100	Lithium ion (Cylindrical)	1100	3.7	1
RD IFR18650-1200	Lithium ion (Cylindrical)	1200	3.7	1
RD IFR18650-1500	Lithium ion (Cylindrical)	1500	3.7	1
RD IFR22500-1700	Lithium ion (Cylindrical)	1700	3.7	1
RD IFR22650-2400	Lithium ion (Cylindrical)	1200	3.7	1
RD IFR26650-3000	Lithium ion (Cylindrical)	1500	3.7	1
RD IFR26650-3200	Lithium ion (Cylindrical)	1600	3.7	1

[d] These cells and batteries are rechargeable. The circuitry containing these cells or batteries is to contain protective components intended to protect the cells or batteries from currents in excess of the maximum charging current and voltage indicated.

[e] The Max Charging Voltage noted in the column is the maximum voltage employed during the abnormal charging test of the secondary lithium ion cell. However, the maximum recommended charging voltage for lithium ion cells is 4.2 V, unless indicated otherwise.

[f] Test Compliance - The cells comply with the tests in UL 1642 as noted:

- 1 - Complies with all single-cell tests
- 2 - Complies with all single-cell tests except the impact test
- 3 - Complies with all single-cell tests except the projectile test
- 4 - Complies with all single-cell tests except the crush test

Marking: Company name, Recognized Component Mark,  on the cell or smallest shipping package containing the cell.  
Last Updated on 2014-01-14

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".